
GROUP 0

GENERAL

CONTENTS

VEHICLE IDENTIFICATION	0-2	MAJOR SPECIFICATIONS	0-3
-------------------------------------	------------	-----------------------------------	------------

VEHICLE IDENTIFICATION

M4000001000424

MODELS

Model code		Engine model	Price class	Transmission model	Fuel supply system
CU2W	XNMML6	4G63-DOHC (1,997 mL)	Comfort	F5M42 <2WD, 5M/T>	MPI
	XNMMZL6			W5M42 <4WD, 5M/T>	
	XNHMZL6		Sport		
	XNXFZL6	4G63-DOHC I/C-T/C (1,997 mL)	Turbo	W5M51 <4WD, 5M/T>	
CU5W	XNMYZL6	4G69-SOHC MIVEC (2,378 mL)	Comfort	W5M42 <4WD, 5M/T>	
	XRMYZL6			W4A42 <4WD, 4A/T with sport mode>	
	XRMYZR6				
	XNHYZL6		Sport	W5M42 <4WD, 5M/T>	
	XRHYZL6			W4A42 <4WD, 4A/T with sport mode>	
	XRHYZR6				

MAJOR SPECIFICATIONS

M4000003000312

Items		CU2W				
		XNMML6	XNMMZL6	XNHMZL6	XNXFZL6	
Vehicle dimension mm	Overall length	4,545				
	Overall width	1,750		1,780		
	Overall height (unladen)	1,620/1,670* ¹				
	Wheelbase	2,625				
	Track	Front	1,495			
		Rear	1,505			
	Front overhang	945				
	Rear overhang	975				
Ground clearance (unladen)	195					
Vehicle wheel alignment	Front	Toe-in (at the centre of tyre tread) mm	1 ± 2			
		Toe angle (per wheel)	0°03' ± 05'			
		Toe-out angle on turns (inner wheel outer wheel at 20°)	22°00' ± 1° 30'			
		Camber	-0°10' ± 30'* ²			
		Caster	3°15' ± 30'* ²			
		Kingpin inclination angle	12°25' ± 1°30'			
		Side slip (per 1m) mm	0 ± 3			
	Steering angle	Inner wheels	34°50' ± 1°30'			
		Outer wheels (reference)	29°20'			
	Rear	Toe-in (at the centre of tyre tread) mm	3 ± 2			
		Toe angle (per wheel)	0°08' ± 05'			
		Camber	-0°40' ± 30'* ²			
	Wheels and tyres	Tyre size	215/60 R16 95H		215/55 R17 94V	
Wheel size		16 × 6JJ		17 × 6.5JJ		
Offset mm		46		38		

NOTE:

*¹: Vehicles with roof rails.

*²: Difference between right and left wheels must be less than 30'.

Items		CU5W			
		XNMYZL6	XRMYZL6/R6	XNHYZL6	XRHYZL6/R6
Vehicle dimension mm	Overall length	4,545			
	Overall width	1,750		1,780	
	Overall height (unladen)	1,620/1,670* ¹			
	Wheelbase	2,625			
	Track	Front	1,495		
		Rear	1,505		
	Front overhang	945			
	Rear overhang	975			
Ground clearance (unladen)	195				
Vehicle wheel alignment	Front	Toe-in (at the centre of tyre tread) mm	1 ± 2		
		Toe angle (per wheel)	0°03' ± 05'		
		Toe-out angle on turns (inner wheel outer wheel at 20°)	22°00' ± 1° 30'		
		Camber	-0°10' ± 30' ^{*2}		
		Caster	3°15' ± 30' ^{*2}		
		Kingpin inclination angle	12°25' ± 1°30'		
		Side slip (per 1m) mm	0 ± 3		
	Steering angle	Inner wheels	34°50' ± 1°30'		
		Outer wheels (reference)	29°20'		
	Rear	Toe-in (at the centre of tyre tread) mm	3 ± 2		
		Toe angle (per wheel)	0°08' ± 05'		
		Camber	-0°40' ± 30' ^{*2}		
	Wheels and tyres	Tyre size	215/60 R16 95H		
Wheel size		16 × 6JJ			
Offset mm		46			

NOTE:

*1: Vehicles with roof rails.

*2: Difference between right and left wheels must be less than 30'.